

Port-A-Cool Cyclone® 2000



**Centrifugal Air Supply,
1/3 h.p. Two-Speed Motor
Cools 500 sq. ft.**

- Adjustable Louvers
- Quieter Running Centrifugal Fan
- Smaller Footprint

- Lowers temperatures up to 30 degrees F
- Energy efficient 2.5 amps for pump and motor
- Water level sight tube and sump drain
- 3/4" garden hose connection for longer running
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability—near maintenance-free operation
- Shipped completely assembled—ready to operate out of the box
- ETL Listed in U.S. and Canada

Port-A-Cool Cyclone® 2000

Speeds	Two
Air Delivery CFM	1,600 / 2,000
Total Amps	2.5
Water reservoir	10 gallons
Dimensions	31" h x 24" w x 25" d
Unit weight	61 lbs.
Shipping weight	72 lbs.
Box Size	37" h x 25" w x 27" d
Cooling Capacity	500 sq.

**STOCK NUMBER PACCYC02 (BLACK)
STOCK NUMBER PACCYC02A (SIENNA)**