

**STEP 1: Open crate and remove parts**  
(use rubber mallet for disassembly)

- A. Remove screws from 8 corners of knock-down crate
- B. Remove complete roll cage/top assembly from crate

**STEP 2: Install Steering Wheel**

- A. Fit steering wheel over steering wheel shaft
- B. Tighten nut over steering wheel shaft (nut and screws located in small compartment under dash display)
- C. Tighten chrome and black steering wheel cover over the front of steering wheel with 6 screws

**STEP 3: Install Roll Cage/Top**

- A. Remove hardware for attaching roll cage which will already be hand tight located into attaching position on the unit
- B. Attach roll cage/top to unit and tighten all hardware
- C. Attach rear center stabilizer bar to frame using 2 existing bolts

**STEP 4: Install Windshield**

- A. Insert rubber padders into windshield holes and insert the washers into the rubber padders.
- B. Place windshield on unit and then insert rubber strips into each windshield buckle
- C. Lineup windshield buckles on rollbar with windshield holes and secure buckles until tight
- D. When installing top buckle on passenger side, place drop of lubricant or oil on inside rubber strip of buckle to help slide past passenger hand bar and lock into place
- E. Insert screws into windshield holes to secure windshield to windshield buckles and unit.

**STEP 5: Connect Seat Belt & Side Mirrors**

- A. Install mirrors to roll cage using brackets and screws
- B. Bolt seat belt shoulder harnesses to roll cage using bolt/washer already hand tight in attaching position on unit

