

52"

Raptor

The Game Changer.

FEATURES

- Heavy Duty Fabricated Steel Decks - more durable
- 23HP Kawasaki FR Premium Engine - 3 yr warranty
- Fabricated Heavy Duty Steel Frame - Best in Category
- SmoothTrak™ steering
- Patented automatic park brake system, built into levers
- Heavy duty front caster forks with industrial steel ball bearings
- 18" drive tires
- 11" front caster tires
- 3 gal. fuel capacity
- 6 mph

LIMITED
WARRANTY
3 YEAR | **NO**
HOUR LIMIT
RESIDENTIAL

* See your local Hustler dealer for complete warranty details



www.hustlerturf.com

HUSTLER 
Cutting Grass Not Corners

Raptor

Engines

Kawasaki
FR691V
23 hp

More Engine Information:

• www.kawpower.com

ENGINE

Ignition: Electronic

Charging System: 12-volt (see engine manufacturer specs)

Fuel: Unleaded gasoline

Cooling: Air cooled.

TRACTION DRIVE SYSTEM

Type: Dual hydrostatic. Hydro-Gear EZT integrated transmissions.

Transmission Drive: V-belt drive from engine

Ground Speed:

Forward: 0-6 mph (0-9.7 kph)

Reverse: 0-4 mph (0-6.4 kph)

Steering: SmoothTrak™ twin-lever steering allows independent control of each drive wheel.

Turning Radius: True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels.

Brakes:

Service: Hydrostatic braking thru transmissions.

Parking: Automatic parking brake when steering levers are placed in neutral position.

Tires:

Front: 11 x 4.0 – 5, rib tread

Drive: 18 x 8.50 – 8, turf tread

Capacities: Fuel System: 3 US gal (11.36 l)

GENERAL INFORMATION

Safety Features: Operator presence system connected to blade PTO, seat, and park brakes.

Seat: Molded-vinyl seat. Fore and aft adjustment. Suspension springs are standard.

Construction:

Mainframe: 3.25 in x 1.5 in x .120 in (8.3 cm x 3.8 cm x .34 cm) steel channel.

Front caster wheels: Commercial duty with seal roller axle bearings on each wheel. Front caster forks are 1/4in (.64 cm) steel.

Front Axle: Fabricated w/ industrial caster yoke ball bearings.

Controls: Hand-operated choke/throttle, ignition switch, mower clutch PTO switch.

Cup Holder: Cup holder molded into the left side fender. Accommodates nearly any cup size.

Storage Area: Both fenders.

DIMENSIONS

Height: 39 in (99 cm)

W/52 in Deck

Length: 73 in (185 cm)

Overall width: 53.4 in (135.6 cm) w/ discharge chute up

Tire-to-tire width: 41 in (104 cm)

Weight: 526 lbs (238.59 kg)

DECKS

Side-Discharge: 52"

Type: 52" deck 3 blades. Deck-mounted anti-scalp wheel(s) for improved flotation in rolling and uneven terrain.

Construction: 11 ga, .120 in (.30 cm) welded steel with reinforced spindle mount areas. Solid 1/4in. thick steel bars to protect impact areas and trim edges. 4 in (10.16 cm) deep deck housing for high-capacity mowing.

52"

Cutting Heights: Hand-operated deck height adjustment. 1/2in. increments from 1.5in. to 4.5in. (3.8cm x 11.43cm)

Mowing Blades: Heavy-duty, heat-treated, low-lift steel blades.

52 in: 3 - 17.86 in x 2.25 in x .188

Deck Drive: V-belt drive to spindles with PTO-electric clutch. Spring tension idler.

Spindles: Die cast aluminum housing, 3/4in. diameter high carbon steel shafts with triple protected sealed ball bearings.

Discharge Chute: High density, rubberized.

Trim Capacity: (left side)

52 in: 6.7 in (17.02 cm)

ACCESSORIES

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings and recycles nutrients back to the soil.

Flex Forks: Shock-absorbing front caster forks for a smooth ride and effortless mowing.

Steering Extension Kit

2-Bag Catcher: 5.2 bushel capacity



*Specifications subject to change without notice.
ANSI CERTIFIED*

