

# FLAT-OUT™ FEEDER

Model No. 65010

## NO ASSEMBLY REQUIRED

Remove all components from box. Remove all packing materials.

### IMPORTANT NOTE:

Before filling feeder, make sure spring-loaded ring located at bottom of fabric liner is pushed down so it is level with top of the feed ports. Sometimes during shipment and use spring-loaded ring will slide up feeder. Pushing it back down insures feed will not get lodged between rings of the feeder.

STEP 1 - Place Flat-Out™ Feeder in a level stable location to assure feeder can collapse properly as feed exits. Position feeder so animals have clear access to both feed ports.

STEP 2 - Remove lid from Flat-Out™ Feeder. Remove 2 prop-rods from storage clips on the cross-bar(Figure 1). Assemble 2 prop-rods by threading them together.

STEP 3 - Lift cross-bar until Flat-Out™ Feeder is fully extended. Insert the assembled prop-rod beneath the cross-bar to hold feeder up while filling (Figure 2).

STEP 4 - Fill Flat-Out™ Feeder with up to 300lbs of feed. DO NOT OVERFILL. Feed caught between fabric liner and overlapping rings of barrel can interfere with the collapsing operation.

STEP 5 - Remove prop-rod and allow feeder to collapse until cross-bar comes to rest on feed. Unthread prop-rod and store 2 pieces of prop-rod in storage clips on cross-bar.

STEP 6 - Replace lid on feeder and secure both latches.

STEP 7 - Flat-Out™ Ground Feeder is ready for feeding. Remember when you return, check feeder from a distance. When feeder returns to its smallest shape, it is time to refill.

NOTE: Before refilling, raise and lower the feeder a few times to allow debris to exit feeder. Debris can cause feeder not to fully collapse.

### MAINTENANCE:

Periodically clean barrel rings and behind fabric liner to remove dust and debris from outside and inside of the barrel. Clean with a damp cloth.

For questions email [service@primos.com](mailto:service@primos.com) or call customer service at (601) 879-9323.

### 1-YEAR LIMITED WARRANTY:

1-Year coverage requires registration. Register Flat-Out™ Ground Feeder by calling customer service or visiting [www.primos.com](http://www.primos.com). For warranty or service information, email [service@primos.com](mailto:service@primos.com) or call customer service at (601) 879-9323.

Primos® Hunting  
604 First St., Flora, MS 39071  
(601) 879-9323 • [www.primos.com](http://www.primos.com)

# FLAT-OUT™ GROUND SETUP AND OPERATION INSTRUCTION MANUAL



(Figure 1)



(Figure 2)

**PRIMOS**  
HUNTING  
SPEAK THE LANGUAGE®