

Key Features

- Axial Cam, Tri-Plex Plunger Pump with Brass Head
- Thermal Relief Valve
- 1.25 in. Diameter Tubular Steel Frame for Protection and Durability
- Removable Handle for Easy Storage
- Low Pressure Chemical Injector for Applying Cleaning Solution
- 4 Stainless Steel Quick Connect Nozzles
- 35 in. Insulated Wand with Quick Connect Coupler
- 25 ft. High Pressure Hose
- 12 in. Never Flat Tires
- Convenient Hose, Gun and Wand Storage on Frame
- Maximum Water Temperature – 104°F (40°C)
- Comfort Grip Trigger Gun

BOX:

G.W.: 87.1 lb.(39.5 kg)
 MEAS.: 29.9 in. X 22.1 in. X 24.2 in.
 76.0 cm X 56.0 cm X 61.5 cm

UNIT:

N.W.: 73.9 lb.(33.5 kg)
 MEAS.: 36.3 in. X 19.9 in. X 38.2 in.
 97 cm X 50.6 cm X 97 cm



1 YEAR LIMITED WARRANTY

Parts & Labor

Champion Power Equipment, Inc.
 10006 Santa Fe Springs Rd. • Santa Fe Springs, CA 90670 • USA
 1-877-338-0999 • www.championpowerequipment.com
 MADE IN CHINA / HECHO EN CHINA / FABRIQUÉ EN CHINE

196cc CHAMPION OHV Engine

- 4 Stroke
- Single Cylinder
- Air Cooled
- Low Oil Shut-Off
- Recoil Start
- Cast Iron Sleeve for Durability

quickCONNECT Nozzles included

