

2990 LB GVWR TRAILER



SPECIFICATIONS

- 2,990 lb. GVWR (Gross Vehicle Weight Rating)
- Main Frame 3" x 2" Angle
- 15" Tires Rated 1,820 lbs. each
- Fully Lighted to D.O.T. Requirements
- 2" A-Frame Coupler w/Safety Chains
- Pressure Treated Floor
- 3,500 lb. Cambered Axle
- Ramp Gate for Easy Loading
- Side Ramp Gate 60" Right Side Forward of Fender
- 2,000 lb. Top-Wind Jack
- Wire in Protective Conduit

REPLACEMENT PARTS

PART#	DESCRIPTION	IMAGE
TSC# 3014040	TIRE & WHEEL ST205 X 15 IN.	A
8874/TSC# 0175423	88X74 IDLER AXLE 3,500 LBS. for the 6' wide	B
120/TSC# 1075244	HUB DUST COVER	C
143/TSC# 1750064	2" COUPLER REPAIR KIT	D
545/TSC# 0175009	1,750 LBS. HUB KIT 5-HOLE	E
350/TSC# 0175203	1-3/8" SPINDLE KIT	F
639/TSC# 1091208	CLASS II SAFETY CHAIN	G
9320/TSC# 0188183	32" STEEL FENDER	H
502/TSC# 1075024	1-3/8" BEARING KIT	I

6'X12' ATV TRAILER SIDE GATE
SKU# 1091046
1,850 LB PAYLOAD CAPACITY

**TRACTOR SUPPLY
EXCLUSIVE**

7'X12' ATV TRAILER SIDE GATE
SKU# 1090286
1,800 LB PAYLOAD CAPACITY

- 6' 10" Width

