



Custom Metal Products, LLC

5781 Westwood Dr. Weldon Spring, MO 63304

636-329-0142 www.CustomMetalProd.com

Tactical Combo Base/Target Assembly Instructions

- 1) Place base on ground, and slide the stabilizer legs into the sockets. The legs can be adjusted for uneven ground.
- 2) Cut 2X4 post to the desired length.
- 3) Place post into base, place cap on post.
- 4) Install target by bolting to the cap using the Grade 8 Carriage bolt and locknut supplied. Place a flat washer between the target and the bracket to enhance the ringing sound.
- 5) When used as a paper target stand, remove the 2x4 and install 1x2 into the two sockets provided. Staple the paper/cardboard target to the 1x2's.
- 6) After reading the Care and Use instructions below, the target is ready to shoot.



Optional Hostage Head Add-on

Replace standard Target Mounting Cap with the combination Hostage Head Add-On.

Bolt Torso Target to the front of the cap and slide over the top of the 2x4 post.

Always wear approved safety glasses and ear protection when shooting or observing shooting at any target.

Target Use and Care

The targets produced by CMP are made from AR500 steel for long life and minimum damage due to bullet strikes. The stands, bases and mounting brackets are made from normal steel and can be damaged by repeated bullet strikes, and will not withstand rifle bullet strikes. The design of the targets protects much of the base with the AR500 target face, but occasional hits will occur.

- Pistol shooting at our targets should be performed beyond a range of 15 yards.
- 22 rimfire pistol and rifle shooting at our targets should be performed beyond a range of 15 yards
- Rifle (below 3000 feet per second at impact) shooting at our targets should be performed beyond a range of 100 yards.
- Never use armor piercing or steel core bullets to shoot any target
- Always place the target in front of a backstop to capture any bullets which miss the target.
- Always inspect the targets and support structure before and after use for damage and for proper and safe operation.
- Do not use any targets or support structure if any damage or improper operation is found.
- When the first face gets pockmarked or damaged, turn target over and use other face.

Warranty

All CMP products are warranted for one year from date of purchase for defects in material or workmanship. We will repair or replace, at our option, any component found to be defective. Shipping of product back to the manufacturer is the responsibility of the customer. Contact CMP for return shipping instructions.

Limitations of warranty: This warranty does not cover normal wear items such as bolts, nuts, springs, etc. The target faces will become dented and pock marked due to repeated bullet strikes, this is normal wear and is not covered by the warranty. This warranty does not cover any item that has been modified or altered in any way, used outside its intended purpose, or damaged by acts of nature.