



Custom Metal Products, LLC

5781 Westwood Dr. Weldon Spring, MO 63304

636-329-0142 www.CustomMetalProd.com

E-Type Static Stand and Target Assembly Instructions



1) Place target on table with end of target with holes off the table, or place on ground with blocks under the end with holes. Assembly is a two man operation. Place the two Grade 8 Carriage bolts in the holes. Never use a lower grade bolt, as they may be damaged by the impacts.



2) Place the post assembly on the two bolts. Install the two hardened flat washers and locknuts and tighten securely.



3) Place the base at the desired target position, and slide the two stabilizer legs into the sockets at the ends of the base assembly.



4) Lining up the V of the post with the V of the base, lower the Target/Post assembly into the socket in the base.

After reading the care and use instructions on the rear, the target is ready for use.

Always wear approved safety glasses and ear protection when shooting or observing shooting at any target.

Target Use and Care

The targets produced by CMP are made from AR500 steel for long life and minimum damage due to bullet strikes. The stands, bases and mounting brackets are made from normal steel and can be damaged by repeated bullet strikes, and will not withstand rifle bullet strikes. The design of the targets protects much of the base with the AR500 target face, but occasional hits will occur.

- Pistol shooting at our targets should be performed beyond a range of 15 yards.
- 22 rimfire pistol and rifle shooting at our targets should be performed beyond a range of 15 yards
- Rifle (below 3000 feet per second at impact) shooting at our targets should be performed beyond a range of 100 yards.
- Never use armor piercing or steel core bullets to shoot any target
- Always place the target in front of a backstop to capture any bullets which miss the target.
- Always inspect the targets and support structure before and after use for damage and for proper and safe operation.
- Do not use any targets or support structure if any damage or improper operation is found.
- When the first face gets pockmarked or damaged, turn target over and use other face.

Warranty

All CMP products are warranted for one year from date of purchase for defects in material or workmanship. We will repair or replace, at our option, any component found to be defective. Shipping of product back to the manufacturer is the responsibility of the customer. Contact CMP for return shipping instructions.

Limitations of warranty: This warranty does not cover normal wear items such as bolts, nuts, springs, etc. The target faces will become dented and pock marked due to repeated bullet strikes, this is normal wear and is not covered by the warranty. This warranty does not cover any item that has been modified or altered in any way, used outside its intended purpose, or damaged by acts of nature.

10/7/2013