

Model 6917-0 (49ST/Canada)
UPC: 696471069174

1 of 2



FEATURES

- EASY PRIME™ Funnel design for quick and easy priming
- Hose kit included - 10' suction hose, 25' of discharge hose, garden hose attachment, strainers, and connectors
- Powerful Generac Pump - Can pump up to 30 gallons per minute
- Color coded suction and discharge ports to ensure the correct hose connections
- Durable design - Carbon Ceramic Seal, Cast Iron Volute and Impeller
- Generac 34cc OHV engine provides a long engine life

Specifications

Engine Type	4 cycle/OHV
Engine Displacement (cc)	34
Start Type	Recoil Pull Start
Low Oil Shutdown Method	N/A
Recommended Oil	10W-30 / SAE30
Fuel Capacity (gal/l)	0.4/1.5
Max Run Time	1.0 hrs
Flow gpm/lpm	30/114
Max Total Head (ft/m)	100/30.5
Max Suction Lift (ft/m)	26/7.9
Mechanical Seal Type	Carbon Ceramic
Solid Handling (in)	N/A
Suction Port (NPT)	1.0
Discharge Port (NPT)	1.0
Pump Housing	Aluminum
Impeller	Cast Iron
Volute	Cast Iron

Hose Kit Included	Yes
Discharge Hose Length (ft/m)	25/7.6
Suction Hose Length (ft/m)	10/3
Hose Connections	Plastic Speed Nut
Strainer	Plastic
Wheel Kit	N/A
Country of Origin	China
Warranty	1 Year
Manual Part #	0K9077
Length (L) (in/mm)	13.9/325
Width (W) (in/mm)	9.7/247
Height (H) (in/mm)	13.5/343
Unit Weight (lbs/kg)	16.5/7.5
Carton Length (in/mm)	18.2/463
Carton Width (in/mm)	15.2/385
Carton Height (in/mm)	15.8/402
Shipping Weight (lbs/kg)	26.9/12.2

