


THRU-THE-WALL AIR CONDITIONERS

**4PATW I2000**



|                                       |  |
|---------------------------------------|--|
| <b>UPC Code:</b>                      | 8-42149-02567-0  |
| <b>Cooling Capacity:</b> (BTU)        | 12,000   |
| <b>Coverage:</b> (sq. ft)             | 450–550  |
| <b>EER Certified:</b>                 | 10.5   |
| <b>Energy Star Rated:</b>             | Yes  |
| <b>Fan Speeds:</b> (cool/fan)         | 3/3  |
| <b>Amps:</b>                          | 10.0   |
| <b>Watts:</b>                         | 1,142  |
| <b>Decibels:</b> (Hi/Mi/Lo)           | 61/59/57   |
| <b>Interior trim kit included:</b>    | Yes  |
| <b>Fits standard wall sleeves:</b>    | Yes (sold separately)  |
| <b>Unit Dimensions:</b> (WxHxD in.)   | 24 <sup>1/4</sup> x 14 <sup>1/2</sup> x 20 <sup>1/2</sup>  |
| <b>Pkg Dimensions:</b> (WxHxD in.)    | 28 x 17 x 26 <sup>3/4</sup>  |
| <b>Stuffing Qty:</b> (20'/40'/40' HQ) | 120/255/306  |
| <b>Weight:</b> (net/gross lbs)        | 76/87  |
| <b>Refrigeration:</b>                 | R410A  |
| <b>Outlet Configuration:</b>          | <br>15 AMP 115V |



**FEATURES**

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Full function remote control
- Auto, Sleep, Dry and Energy Saver modes
- 24 hour timer
- Auto restart function
- Slide-out filter access



**FOLLOW ME**  
 REMOTE CONTROL FEATURE  
 (Portable Thermostat for  
 TOTAL Room Coverage)