

Quick **SETUP** Guide

Assembling Your Generator

1 Verify Components

Owner's Manual & Product Registration Guide

2

3

4

3 Remove and discard existing bolt and save nut.

RE-USE nut.

4

Add ENTIRE bottle (1 quart) of engine oil.

Do not fill past threading!
Replace oil cap after filling.

5

Do not fill past this lip!
Replace Gas cap.

E85 **E20**

Never add fuel while unit is running or hot!

Quick **START UP** Guide

Starting Your Generator

Model #s: 5622-0, 5736-0, 5623-0, 5698-0, 5737-0, 5700-0, 5698-0, 5738-0, 5690-0

1 **NOTICE!**
This quick start guide is not meant to replace the owner's manual that was shipped with this unit. For complete safety, operating and maintenance instructions, read the owner's manual completely **BEFORE** using this equipment.

DANGER

Using a generator indoors CAN KILL YOU IN MINUTES.
Generator exhaust contains carbon monoxide. This is a poison you cannot see or smell. NEVER use inside a home or garage, EVEN IF doors and windows are open. Only use OUTSIDE and far away from windows, doors, and vents.

2 Check Oil Level.

3 Check Fuel Level.

4 Turn Fuel Shut Off Valve to ON.

OFF
ON

5 Turn engine switch to ON. Do NOT start generator with cords plugged in. For CARB/CSA units, turn breaker switch OFF before starting unit.

CARB/CSA units only

6 Pull Choke.

7 Pull Recoil Handle.

8 Engine STARTS RUNNING Engine

9 Plug in cords AFTER generator is running. Unplug devices before stopping engine.