

**Quick SETUP Guide**

**Assembling Your Generator**

**1 Verify Components**

Owner's Manual & Product Registration Guide

**2**

**3**

**4**

**3** Remove and discard existing bolt and save nut.

RE-USE nut.

**4**

Add ENTIRE bottle (1 quart) of engine oil.

Do not fill past threading! Replace oil cap after filling.

**5**

Do not fill past this lip! Replace Gas cap.

UNLEADED GASOLINE

**E85** **E20**

Never add fuel while unit is running or hot!

**Quick START UP Guide**

**Starting Your Generator**

Model #s: 5622-0, 5736-0, 5623-0, 5698-0, 5737-0, 5700-0, 5698-0, 5738-0, 5690-0

**1** **NOTICE!**  
This quick start guide is not meant to replace the owner's manual that was shipped with this unit. For complete safety, operating and maintenance instructions, read the owner's manual completely BEFORE using this equipment.

**DANGER**

**Using a generator indoors CAN KILL YOU IN MINUTES.**  
Generator exhaust contains carbon monoxide. This is a poison you cannot see or smell. NEVER use inside a home or garage, EVEN IF doors and windows are open. Only use OUTSIDE and far away from windows, doors, and vents.

**2** Check Oil Level.

**3** Check Fuel Level.

**4** Turn Fuel Shut Off Valve to ON.

OFF

ON

**5** Turn engine switch to ON. Do NOT start generator with cords plugged in. For CARB/CSA units, turn breaker switch OFF before starting unit.

On

Off

CARB/CSA units only

**6** Pull Choke.

**7** Pull Recoil Handle.

**8** Engine STARTS RUNNING Engine

**9** Plug in cords AFTER generator is running. Unplug devices before stopping engine.