

HDPE

- Manufactured with smooth interior allowing for more efficient flow
- Designed with a bell and spigot with a gasket for a water tight joint
- Excellent Abrasion and Corrosion resistance
- Long term drainage solution
- High Density Polyethylene

Specs:

- Meets or exceeds AASHTO M252 and AASHTO M294 Type S

| Size | Length | Width | Height | Weight |
|----------|--------|--------|--------|--------|
| 20' HDPE | | | | |
| 12" | 20' | 14.75" | 14.75" | 64 |
| 15" | 20' | 17.75" | 17.75" | 99 |
| 18" | 20' | 20.75" | 20.75" | 129 |
| 24" | 20' | 26.75" | 26.75" | 231 |

Galvanized Corrugated Steel Pipe

- Used in driveway and roadway culverts
- Durable and easy to install
- Constructed of 16 gauge galvanized steel
- Designed with re-corrugated ends for coupling ease
- Long term drainage solution

Specs:

- Meets or exceeds AASHTO M36, ASTM A760 AASHTO M246, ASTM A929

| Size | Length | Width | Height | Weight |
|----------------|--------|--------|--------|---------------|
| 10' Galvanized | | | | (Approximate) |
| 12" | 10' | 13" | 13" | 88 |
| 15" | 10' | 16" | 16" | 108 |
| 18" | 10' | 18.75" | 18.75" | 132 |
| 24" | 10' | 24.75" | 24.75" | 175 |
| 20' Galvanized | | | | |
| 12" | 20' | 13" | 13" | 176 |
| 15" | 20' | 16" | 16" | 215 |
| 18" | 20' | 18.75" | 18.75" | 263 |
| 24" | 20' | 24.75" | 24.75" | 349 |