

Eagle PVC Suction Hose

Green/Clear PVC Suction & Discharge Hose

Applications:

- Agricultural liquid fertilizer
- Air seeder lines
- Drain lines
- Irrigation lines
- Rock dusting
- Pumps, rental and construction dewatering
- Pumps, trash
- Mining applications (MSHA approved)
- Water suction – standard duty



Tube: PVC tube with rigid PVC helix

Temperature: -10°F to +140°F

Couplings: * Contact JGB for proper fitting recommendation and coupling procedure.

* MSHA Approved

Features:

- Smooth both inner & outer surface
- Ellipse shaped helix: sustains strength without added thickness
- Lightweight, highly flexible - excellent vacuum rating
- Transparent construction allowing visual confirmation of material flow

Part #		ID	OD	Min. Bend Radius	WP	Vacuum Rating	Burst Pressure (psi)			Weight	Standard Length
Clear	Green						water temp				
		in	in	in	psi	in/Hg	50°F	96°F	122°F	lbs	ft
007-0160-0085I	007-0169-0085I	1	1.24	3	85	29	313	256	185	0.26	100
007-0200-0085I	007-0209-0085I	1-1/4	1.54	4	85	29	284	228	156	0.34	100
007-0240-0070I	007-0249-0070I	1-1/2	1.82	5	70	29	270	213	142	0.44	100
007-0320-0065I	007-0329-0065I	2	2.28	8	65	29	242	199	128	0.55	100
007-0400-0050I	007-0409-0050I	2-1/2	2.83	10	50	29	228	185	128	0.79	100
007-0480-0060I	007-0489-0060I	3	3.35	12	50	29	199	171	100	0.97	100
007-0640-0050I	007-0649-0050I	4	4.45	14	50	29	199	171	100	1.71	100
007-0960-0040I	007-0969-0040I	6	6.67	25	30	28	156	114	57	3.70	100/20
007-1200-0040I	007-1289-0040I	8	8.83	30	30	28	156	114	57	6.05	20