

EZ Kote®

Airless Paint Spray Hose

- Application:** A high pressure conductive hose suitable for conveying paints, fuels, oils, and most other solvents. EZ Kote® is recommended for applications where an electrostatic charge must be eliminated.
- Tube:** Extruded, seamless nylon
- Reinforcement:** High tensile synthetic
- Cover:** Abrasion-resistant polyurethane
- Temperature:** 0° to 200°F
- Packaging:** Cut to length and coupled
- Branding:** E-Z Kote® Wireless Antistatic Hose 1/4" ID Max W.P. 3300psi 228bar
- Lengths:** Made to order lengths available in all sizes.
1/4" 25 ft, 50 ft assemblies.
3/8" 50 ft assemblies.
3/16" Whip hose in 3 ft, 5 ft, or 6 ft lengths.
- Couplings:** 1/4" or 3/8" female swivels; male NPT with spring guards



Features:

- Special construction keeps hose lightweight and flexible.
- A special static drain element dissipates static charge.
- Date coding on the coupling provides traceability.
- A high pressure conductive hose

Part #	Nom ID	Nom OD	Bend Radius	Min Burst	WP	Weight
	in	in	in	psi	psi	lbs/100 ft
016-0032-350P	3/16	.432	1.8	14,000	3500	4.8
016-0046-330P	1/4	.491	2.5	13,200	3300	5.0
016-0060-300P	3/8	.660	3.5	13,200	3300	8.7

Connect with us:



www.jgbhose.com

JGB Headquarters
115 Metropolitan Dr.
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
2540 Walden Ave.
Cheektowaga, NY 14225
(716) 684-8224

Southeast Regional Hub
1407 Westinghouse Blvd.
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
9707 Green Park Industrial Dr.
St. Louis, MO 63123
(314) 487-3144

Williston Branch
520 Bean Dr.
Williston, ND 58801
(701) 570-2945

Houston Branch
619 E. Sam Houston Pkwy.
Suite 200
Pasadena, TX 77503
(281) 930-7777