

JGB Enterprises



Water Suction
& Discharge

Eagle Pump[®] HD

Eagle Pump[®] HD 150 PSI Rubber Suction Hose

Application: Water suction and discharge in industrial and construction services.

Tube: Natural and Synthetic Rubber

Reinforcement: High tensile synthetic textile and steel helix wire

Cover: Abrasion and weather resistant synthetic rubber

Temperature: -22°F to + 185°F

Branding: EAGLE PUMP[®] HD 150 PSI MAX



Part #	ID	OD	WP	Burst	Bend Radius	Weight
	in	in	psi	psi	in	lbs/ft
004-0242-0150I	1-1/2	1.89	150	450	5	.73
004-0322-0150I	2	2.44	150	450	7	1.2
004-0482-0150I	3	3.50	150	450	12	1.9
004-0642-0150I	4	4.53	150	450	17	2.6
004-0962-0150I	6	6.61	150	450	27	4.9
004-1282-0150I	8	8.86	150	450	43	7.2
004-1602-0150I	10	10.98	150	450	59	12.2
004-1922-0150I	12	12.95	150	450	75	13.79

Download the JGB[®] Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777