

# SUB-COMPACT 3-POINT SPECIFICATIONS

## BOX BLADE

<b>BBSCT4</b>	
Horsepower	17-25
Hitch Type	Cat 0 Spacing (cat 1 pins installed)
Working Width	49.25"
Height of Molboard	12.25"
Side Panels	1/4" thick
Depth of Bucket	18"
Height	32"
Weight (lb)	270 lbs.
Number of Shanks	4
Vertical Shank Position	4 position/ and removable (1.5" increments from 3"- 9" below sideplates)
A-Frame Material	0.375" steel
Cutting Edges	2- 3/8"x6" high carbon heat treated blades (replaceable)
Shank Beam	2"x4" rectangle tubing 1/4" thick

## GRADER BLADE

<b>RBSCT5</b>	
Horsepower	18-32
Hitch	Cat 0 Spacing (cat 1 pins installed)
Working Width	60"
Weight	168 lbs.
Angling	5 FWD/ 5 REV up to 45 degree right or left
Molboard Height	12.5"
Molboard Thickness	1/4"
Cutting Edge	3/8"x6" high carbon heat treated blades (replaceable)

# SUB-COMPACT 3-POINT SPECIFICATIONS

## ROTARY TILLER

RTSCT4	
Recommended tractor PTO Horsepower	18-30
Weight	510 lbs.
Working Depth	7"
Working Width	46.5"
Overall Width	53"
Hitch	Cat 0 Spacing (cat 1 pins installed)
Driveline	540 RPM Slip Clutch Protection
Number of flanges on rotor	6
Number of tines per flange	4
Rotor Rotation	Reversible (FWD/ REV)
Rotor Shaft Speed	211 rpm @ 540 rpm PTO
Skid shoes	Adjustable (0.5", 1", 2")
Top Gearbox construction	Cast Iron Housing, Hardened Steel Gears
Side Drive construction	Chain Drive
Top Gearbox lubrication	90W gear oil (GL5-85W 140)
Side Drive lubrication	EP00 oil (Double Zero Grease)

# SUB-COMPACT 3-POINT SPECIFICATIONS

## LANDSCAPE RAKE

### LRSC5

Horsepower	17-32
Hitch	Cat 0 Spacing (cat 1 pins installed)
Rake Width	60"
Weight	177 lbs.
Rake Height	21"
Number of Teeth	30
Teeth Spacing	1" gap
Angle and Position	5 FWD/ 5 REV up to 45 degree right or left

## TILLAGE DISC

### DSCT5

Horsepower	18-32
Hitch	Cat 0 Spacing (cat 1 pins installed)
Cultivation Width	62.5"
Height	30.5
Length	53"
Weight	407 lbs.
Number of Disc Blades	16
Disc Blade Types	14"x3mm notched
Disc Blade Spacing	7.5"
Bearing Type (X per gang)	Replaceable sealed, 2 per gang
Gang Axle	2.5-15 degree

# SUB-COMPACT 3-POINT SPECIFICATIONS

## ROTARY CUTTER

RCSCT4	
Weight	350lbs.
Hitch	Cat 0 Spacing (cat 1 pins installed)
Cutting Width	48"
Overall Width	50"
Overall Length (Including Tailwheel)	69"
Deck Height	7.5"
Cutting Height	2" min
Cutting Capacity	<1"
Horsepower	18-32
Power Take-Off Speed	540
Gearbox	45 hp cast iron housing, precision forged steel gears
Gearbox Lubrication & Capacity	EP 80-90W gear oil, 23 ounces
Deck Construction	14 gauge top/ 11 gauge sides.
Stump Jumper	1/8" Thick, Round 22.3" pan-type
Blades	1/2"x3" Heat Treated Free Swinging w/ Suction Lift
Blade Bolt Size	42mm socket
Blade Tip Speed	9,982 ft./min.
Driveline	ASAE Cat 4 Shear Bolt Protection
Driveline Protection Options	Shear Bolt
Tailwheel	dual adjustable height rubber
Safety Guards	Rubber front/rear guards available
Shear Bolt	1/2" x 3-1/2" Grd 2 Hex Bolt
Castle Nut on Gearbox	38mm socket