




235

New model, ideal for jobs like pruning, lighter cutting tasks and hobby work. Easy to start and operate, thanks to built-in Husqvarna features like ergonomic design, facilitating technology and powerful X-Torq® engine with low emissions.




AIR INJECTION

Centrifugal air cleaning system removes larger dust and debris particles before reaching the air filter. This results in reduced air filter cleanings and improved engine life.



X-TORQ®

Delivers lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



COMBINED CHOKE/STOP CONTROL

Allows for easier starting and reduces the risk of engine flooding.



LOWVIB®

System designed to reduce vibration levels to the operator, which lessens fatigue.

Features

- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

Technical data cylinder displacement

34.4 cc

| | |
|--|--------------------------|
| Power output | 1.8hp |
| Idling speed | 3000rpm |
| Maximum power speed | 9000rpm |
| Cylinder bore | 1.5 inch |
| Cylinder stroke | 1.26 inch |
| Ignition system | IIDA |
| Ignition module air gap | 0.01 " |
| Spark plug | NGKBPMR7A |
| Electrode gap | 0.02 " |
| Carburetor model name | ZAMAW29 |
| Fuel tank volume | 0.14 US pint |
| Oil tank volume | 0.09 US pint |
| Oil pump type | Fixed flow |
| Oil pump capacity | 8-8 ml/min |
| Chain pitch | .325" / 3/8" |
| Recommended bar length, min-max | 13"-16" |
| Chain speed at max power | 53.48 fts |
| Equivalent vibration level (ahv, eq) front / rear handle | 3.4/4.5 m/s ² |
| Sound pressure level at operators ear | 98.6 dB(A) |
| Guaranteed sound power level, LWA | 113 dB(A) |
| CE certified | No |
| Weight (excl. cutting equipment) | 10.3 lbs |

ARTICLES

952 80 21-55 16" - 3/8 - SN - EPA - US, CA

\$ 199.95

